



APOLLO

Physical Properties

Weight: Type II 20 oz

Content: 100% Vinyl

Backing: Osnaburg

Width: 52/54"

Repeat: Vertical, Reversible

Performance:

Fire Rating: Class A, ASTM E84

Europe CE Fire Tested

Color Fastness UK Test Result: BS2782-Pass

Meets Federal Specifications CCC-W-408D for scrubbability, washability and stain resistant.

Sustainability:

Low emitting--passes Cal 01350 Standard (Leed EQ 4.2)

NSF 342

Product contains up to 40% recycled content

Free of conflict minerals, heavy metals, solvents, phthalates (BBP, DBP, DEHP, DIDP, DnHP, DnOP), PFC/PFOA

Printed with Solvent-Free Inks

This product has a CE Declaration of of Conformity.

Note:

All wall surfacing materials including wallcoverings, should be selected taking into account the building in which they are to be installed. Buildings that have had liquid or vapor moisture infiltration problems or that have other conditions that make moisture infiltration likely are at risk for mold growth. Should these factors become an issue consult with a professional about the benefits and limitations of wallcovering. All textural type patterns are designed to simulate natural materials. Color, texture and shading should be anticipated as these variations are part of the manufacturing process and add to the richness and beauty of the product.

Manufactured in the USA